

Two-Way Radio

GP3188 Conventional Portable



GP3188

Easy Usage, Great Affordability



KEY ATTRIBUTES AND FEATURES

Crystal Clear Audio

Exceptional audio design for that added communications edge.

Extended Talktime

19hr-talktime on low power and 14hr-talktime on high power for greater productivity.

Battery Latch Lock Feature

Keeps the power source firmly fastened to the radio and allows continuous communication.

Durable and Reliable

Compliant with demanding MIL-STD 810 standards, thus apt for harsh working environments.

Compatible Accessories

Compatible with existing original Motorola and MagOne accessories, thus protecting your investment.

Quick and Easy Programming

Faster programming with the user-friendly Microsoft Windows® based Customer Programming Software.

UNIQUE FEATURES

All features of the GP3188 are available through a single Toggle button. Remarkably clear and reliably rugged, the GP3188's ergonomic design also adds a touch of style.

Voice Operated Transmission (VOX)

Provides total handsfree for maximal productivity.

Battery Indicator

LED provides status of battery life at a glance.

Sticky Permanent monitor

Allows user to stay on monitor mode without consistently pressing the programmable button.

IDEAL FOR:

SECURITY

Call for backup with just a simple, one-button operation of the GP3188. Faster response to emergency situations and intruders means a job well done.

HOSPITALITY

Get compliments, not complaints with prompt, proactive levels of service, thanks to the handy GP3188. Slim, easy to carry around and hands free operation enables staff to meet guest's demands quickly.

MANUFACTURING

Coordination with many people, even across different plants, can be done easily and quickly with the GP3188. Its extended talktime will easily last beyond 12-hour shift

CONSTRUCTION

A harsh environment requires a hardy radio. The GP3188 meets stringent Military Standards 810 C, D, E and F for durability; and loud 500mW speaker ensures clear audio even in high noise environments.

TECHNICAL SPECIFICATION

GP3188 Specifications *				
General	VHF		UHF	
Frequency	136-162MHz, 146-174MHz		403-440MHz, 438-470MHz, 465-495MHz	
Channel capacity	16 channels			
Power supply	7.5V±20%			
Dimensions (without belt clip and antenna)				
With NiCd/extended Lilon	126.5mm (H) x 61.5mm (W) x 45mm (D)			
With standard NMH	126.5mm (H) x 61.5mm (W) x 43mm (D)			
With slim Lilon	126.5mm (H) x 61.5mm (W) x 42mm (D)			
Weight (without belt clip and antenna)				
With extended Lilon			351g	
With slim Lilon			350g	
With standard NMH			417g	
With NiCd			406g	
Average Battery Life@ 5-5-90 Duty Cycle	Hi Power (5W)	Low Power (1W)	Hi Power (4W)	Low Power (1W)
With extended Lilon	14hrs	19hrs	14hrs	19hrs
With slim Lilon	12hrs	17hrs	12hrs	17hrs
With standard NMH	10hrs	13hrs	10hrs	13hrs
With NiCd	8hrs	10hrs	8hrs	10hrs
Receiver⁺	VHF 12.5 kHz	VHF 20/25kHz	UHF 12.5 kHz	UHF 20/25kHz
Frequency	136-162MHz, 146-174MHz		403-440MHz, 438-470MHz, 465-495MHz	
Sensitivity 12dB EIA SINAD	0.25uV		0.25uV	
Adjacent Channel Selectivity	-65dB	-70dB	-60dB	-70dB
Intermodulation	-70dB		-70dB	
Frequency Stability (-30°C to +60°C)	0.00025%		0.00025%	
Spur Rejection	-75dB		-75dB	
Hum and Noise	-45dB@12.5kHz -50dB@25kHz			
Image and 1/2 I-F Rejection	-70dB		-70dB	
Audio Output @ < 5% Distortion	500mW		500mW	
Transmitter	VHF	VHF	UHF	UHF
Frequency	136-162MHz, 146-174MHz		403-440MHz, 438-470MHz, 465-495MHz	
Channel Spacing	12.5/20/25kHz		12.5/20/25kHz	
Frequency Stability (-30°C to +60°C)	0.00025%		0.00025%	
Spurs/Harmonics	-36 dBm < 1GHz -30 dBm > 1GHz		-36 dBm < 1GHz -30 dBm > 1GHz	
Audio Response (from 6dB/oct. Preemphasis, 300 to 3000Hz)	+1, -3dB		+1, -3dB	
Audi Distortion @1000Hz, 60% Rated Max. Dev.	<3%		<3%	
FM Noise	-40dB(12.5KHz) -45dB(25KHz)		-40dB(12.5KHz) -45dB(25KHz)	
FCC Modulation 20/25 kHz	16K0F3E & 11K0F3E		16K0F3E & 11K0F3E	

* Availability subject to country's laws and regulations. Radios meet applicable regulatory requirements.
All specifications subject to change without notice.
Specifications are not representative of all radios and may vary in different radios.
+ All RF readings are typical.

ACCESSORIES FOR GP3188



NNTN4970A -
Slim Lilon
Battery

HMN9021A -
Medium Weight
Dual-Muff
Headset with
Swivel Mic

RLN5238A -
Sports-Style
Headset with in-
line PTT

BDN6646C -
Ear Microphone
with PTT
Interface Module

PMLN4606A -
2Wire
Surveillance Kit
with Clear
Acoustic Tube

ENHANCE YOUR RADIO'S CAPABILITIES

A comprehensive range of accessories is available to suit your needs. With the right combinations of batteries, headsets, carry cases and antenna, it can increase your operational productivity and comfort tremendously. Motorola original accessories are built with the highest quality standards and are specially engineered to ensure maximum performance of your radio.

Programmable Features

- High/Low Power
- System Scan
- Monitor
- Tight/Normal Squelch
- Repeater/Talkaround

ACCESSORIES

BATTERIES
Standard NiMH Battery, 1400mAh
NNTN4851A

Slim Lilon Battery, 1600mAh
NNTN4970A

Extended Lilon Battery, 1800mAh
NNTN4497AR

NiCd Battery, 1100mAh
NNTN4496AR

SINGLE & MULTI UNIT CHARGERS
Desktop Rapid Charger w/US NA Plug
WPLN4138_R

Desktop Rapid Charger w/Euro Plug
WPLN4139_R

Desktop Rapid Charger w/UK Plug
WPLN4140_R

Rapid Charger MUC 120V w/US Plug
WPLN4161AR

Rapid Charger MUC 220V w/Euro Plug
WPLN4162AR

Rapid Charger MUC 220V w/UK Plug
WPLN4163AR

Motorola carries a wide range of audio and carrying solution. Please refer to specified accessories brochures for more information.



Motorola Electronics Pte Ltd
M1C Level 7, 12 Ang Mo Kio Street 64
Ang Mo Kio Industrial Park 3, Singapore 569088
www.motorola.com/governmentandenterprise

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other products or service names are the property of their registered owners. ©Motorola, Inc. 2006
AC3-04-021 Rev.4



Stringent Motorola Accelerated Life Testing simulating five years of hard use in real life. EIA RS-3168 in Shock, Vibration, Dust, Humidity, IP54 for Sealing



Compliance with ISO 9001 Standard on international quality system assurance on design, development, production, installation and servicing of a product.



Stamp of Approval from the U.S. Military for use in rough environment.

